

Portland Cement Samples 183 & 184

Please Note:

- Portland Cement No. 183 is a ASTM C150 Type I/II **with 0.9% slag addition** and No. 184 is a ASTM C150 Type I/II cement **with 0.75% CKD addition**.
 - Adjust phase calculations for additions content
 - See next page for composition of additions
 - Excel spreadsheet is available to assist in making phase calculations.
- Perform fineness tests on cement taken from the 7,800 g physical sample.
- If the ASTM Reference Method is not used to determine the LOI, briefly describe the method used.
- Heat of Hydration test results by ASTM C1702 Isothermal Conduction Calorimetry are now being accepted.
- Please allow until January 27th for receipt of samples.

How to Submit Test Results:

- On the [CCRL home page](#), enter your lab number and PIN and click on 'login'.
- Click on 'Enter Portland Cement Data'.
- Make sure the information at the top of the screen is accurate.
- Carefully enter your data. Round data properly. Data that is not rounded correctly cannot be submitted until correction is made.
- DO NOT enter 'N/A' or zeros for data that you are not reporting, leave this data area blank. Zeros will be interpreted as data.
- Once all data has been entered click on the 'Submit' button.
- You should see a confirmation screen and receive a confirmation email. Print the confirmation screen for your records.
- If you have trouble entering or do not receive confirmation visit '[Data Entry Trouble Shooting](#)' or contact CCRL.
- **Sign out of the website and login again to check that your data was submitted properly.** You may add data or make corrections up to the closing date.
- The closing date for test results is March 2, 2012 (March 9th for 28-day results).

CCRL Portland 183	
Oxides	Inorganic processing addition
SiO ₂	37.7
Al ₂ O ₃	7.6
Fe ₂ O ₃	0.3
CaO	34.9
SO ₃	0.6
Ingredient % by mass	
Inorganic processing addition (slag)	0.9

CCRL Portland 184	
Oxides	Inorganic processing addition
SiO ₂	19.43
Al ₂ O ₃	4.95
Fe ₂ O ₃	2.75
CaO	59.14
SO ₃	5.74
Ingredient % by mass	
Inorganic processing addition (CKD)	0.75



January 16, 2012

TO: Participants in the CCRL Portland Cement Proficiency Sample Program

SUBJECT: Portland Cement Proficiency Samples No. 183 and No. 184

The current pair of samples in the Portland Cement Proficiency Sample Program has been sent to your laboratory. The samples for the physical tests are packaged in plastic bags and weigh approximately 7800 grams each. The samples for chemical analysis are in glass vials and weigh approximately 30 grams each. **Portland cement No. 183 is an ASTM C150 Type I/II with 0.9% slag addition and Sample No. 184 is an ASTM C150 Type I/II with 0.75% CKD addition.**

Please allow until January 27, 2012 for receipt of these samples. If the samples have not been received on this date or if the samples you receive are damaged, notify us by sending email to ccrl@astm.org or by calling 240-436-4800.

Instruction covering the proposed tests and the necessary data sheets for reporting the test results are on the following pages. Read these carefully before testing.

Chemical Tests: These cements contain inorganic processing additions. Make the appropriate adjustments to the phase calculations. The composition of the additions are provided and an Excel spreadsheet is available to assist in making the phase calculations.

Each sample should be tested separately. The tests should be made as soon as possible, and the results should be promptly submitted upon completion. Test results should be entered at our website: <http://www.ccrl.us/>. The closing date for test results is March 2, 2012. The results for 28-day tests can be entered until March 9, 2012. You will receive notice and information by email when the final report is available at our website.

Additional samples of this sample pair and past CCRL samples are available for sale. These samples can be used for research, technician training, and test equipment verification. Contact us for availability and pricing.

Sincerely,

Robin K. Haupt
Supervisor, Proficiency Sample Programs
Cement and Concrete Reference Laboratory

INSTRUCTIONS FOR TESTING

The two samples for the physical tests are packaged in plastic bags, each of which contains approximately 7800 grams of cement. The two samples for chemical analyses (two additional samples are included for laboratories receiving “secondary” chemical samples) are sealed in glass vials, each of which contains approximately 30 grams of cement. The physical and chemical samples for the odd numbered sample represent one cement, and the physical and chemical samples for the even numbered sample represent another cement. The odd and even numbered samples should not be combined. **The odd numbered sample (no. 183) is Type I/II cement 0.9% slag addition , and the even numbered sample (no. 184) is Type I/II cement with 0.75% CKD addition.** In order to eliminate unnecessary variations in test results, one operator should perform a test method on both samples on the same day.

PHYSICAL TESTS

Prior to testing, pass the cement for the physical tests through a No. 20 sieve in accordance with ASTM Specification C183.

Perform fineness tests on cement taken from the 7,800 g sample.

Insofar as your laboratory is prepared to do so, perform the following physical tests on each sample in accordance with the current ASTM methods designated below.

Normal Consistency	ASTM C187-11
Time of Setting, Vicat	ASTM C191-08
Time of Setting, Gillmore	ASTM C266-08
Soundness, Autoclave	ASTM C151-09
Air Content	ASTM C185-08
Compressive Strength (nine cube batch; 3, 7, and 28 day)	ASTM C109-11
Fineness, Air Permeability	ASTM C204-07
Fineness, Wagner Turbidimeter	ASTM C115-10
Fineness, by the 45 µm (No. 325) Sieve	ASTM C430-08
False Set Test (Paste Method)	ASTM C451-08
Expansion of Portland Cement Mortar Bars in Water	ASTM C1038-10
Heat of Hydration	ASTM C186-05
Heat of Hydration by Isothermal Conduction Calorimetry	ASTM C1702- 09a

It is preferred that the one operator make the physical tests on both samples, on the same day.

CHEMICAL TESTS

Perform the following chemical tests in accordance with ASTM C114-11a and ASTM C150-11 on each sample. There are two chemical analysis programs. The "Primary Chemical Analysis" program is the laboratory's "best effort" and should be the method used to qualify cement, or test cement for acceptance or rejection. A "Secondary Chemical Analysis" program is also available for laboratories that want to submit a second set of results. For more information about the two chemical analysis programs please read "Information on CCRL Chemical Analysis Program" included with the following pages.

Silicon dioxide,	SiO ₂	Titanium dioxide,	TiO ₂
Aluminum oxide,	Al ₂ O ₃	Sodium oxide,	Na ₂ O
Ferric oxide,	Fe ₂ O ₃	Manganic oxide,	Mn ₂ O ₃
Calcium oxide,	CaO	Zinc oxide,	ZnO
Free calcium oxide (free lime)		Chloride,	Cl
Magnesium oxide,	MgO	Chromium oxide,	Cr ₂ O ₃
Sulfur trioxide,	SO ₃	Tricalcium silicate ¹ ,	C ₃ S
Loss on ignition		Dicalcium silicate ¹ ,	C ₂ S
Insoluble residue		Tricalcium aluminate ¹ ,	C ₃ A
Potassium oxide,	K ₂ O	Tetracalcium aluminoferrite ¹ ,	C ₄ A.
Phosphorus pentoxide,	P ₂ O ₅		

¹ value calculated as shown in annex A2 of ASTM C150-11

It is preferred that one chemist make the chemical tests on both samples, on the same day. The results of a single determination should be reported rather than the average result of duplicate determinations.

IMPORTANT NOTE: You are now asked to indicate if the XRF instrument was energy dispersive or wavelength dispersive. And what type of XRF sample preparation, glass disk or pressed powder, was used.

INSTRUCTIONS FOR REPORTING

For the sake of uniformity, report the values for the various tests to the nearest significant number indicated on the reporting forms. Be sure to indicate what chemical analysis procedure was used.

Test results should be entered at our website: <http://www.ccrl.us/>. The closing date for test results submitted through our website will be March 2, 2012. The results for 28-day tests will be accepted until March 9, 2012.

**CEMENT AND CONCRETE REFERENCE LABORATORY
PORTLAND CEMENT PROFICIENCY SAMPLE PROGRAM**

INFORMATION ON CHEMICAL ANALYSIS PROGRAM

The chemical program consist of a "Primary" analysis program and a supplemental "Secondary" analysis program. The "Primary" is the main chemical analysis report. Test results reported as primary analysis must be results a laboratory used to qualify cement, or test cement for acceptance or rejection. Any method of analysis (wet, x-ray, AA, etc.) is acceptable. This analysis represents a laboratory's best effort and will be used to judge the laboratory's testing proficiency.

A supplementary "Secondary" analysis is also available for laboratories that want to report a second set of test results. This secondary analysis could be performed by a second technician or analyzed by a different method. Each laboratory's "secondary" analysis would be compared to statistical values from the "primary" analysis to assign their laboratory ratings. A laboratory must participate in the "Primary" analysis to be eligible to participate in the "Secondary" analysis.

If your laboratory is not currently receiving a "Secondary" chemical analysis sample and would like to participate in this program you may do one of the following: 1) subscribe to receive future samples (including the current pair) or, 2) you may request just the current pair of samples. To enroll select one of the options by checking the appropriate box, complete laboratory information, include payment for the amount indicated, and return to CCRL. Contact us if you have any questions.

NOTE: **Do not complete this form** if your laboratory currently receives the Secondary Analysis Chemical Report.

Check the appropriate box:

- Send a report for the "Secondary Chemical Analysis" of the current pair of samples only (\$87.00) for the January 2012 samples).

Company _____

Location _____

CCRL lab number _____

Requested by _____

Date _____

Phone: _____ Email: _____

RETURN TO:

R. K. Haupt, Supervisor, PSP
Cement and Concrete Reference Laboratory
4441 Buckeystown Pike, Ste C
Frederick, Maryland 21704
Fax: 610-834-7066

**CCRL PROFICIENCY SAMPLE PROGRAM
PORTLAND CEMENT SAMPLES NO. 183 AND NO. 184
PRIMARY CHEMICAL ANALYSIS REPORT FORM**

RETURN TO: R.K. Haupt, Supervisor, PSP
Cement and Concrete Reference Laboratory
4441 Buckeystown Pike, Ste C
Frederick, Maryland 21704
Fax: 610-834-7066

FROM: _____

e-mail: _____
Check here if name or address has changed _____

PRIMARY CHEMICAL ANALYSIS

NOTE: Test results reported on this form should be the laboratory's "best effort". The method used should be the method used to qualify cement, or test cement for acceptance or rejection. More information about this program and the Secondary Analysis program is available on the page titled "Information on CCRL Chemical Analysis Program".

	Sample No. 183	Sample No. 184	Test ID	X-ray *	ASTM Alternate Wet Method	ASTM Reference Wet Method	A.A.	Other (specify)
Report values below to nearest 0.01%				Check the method used				
Silicon dioxide, SiO ₂			10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Aluminum oxide, Al ₂ O ₃			21	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Ferric oxide, Fe ₂ O ₃			30	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Calcium oxide, CaO			40	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Free Calcium oxide			41	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Magnesium oxide, MgO			50	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Sulfur trioxide, SO ₃			60	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Loss on ignition			70	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Briefly describe LOI procedure:								
Insoluble residue			80	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Potassium oxide, K ₂ O			100	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Titanium dioxide, TiO ₂			103	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<p>*Please provide the following information the XRF equipment used for these results.</p> <p>XRF instrument: <input type="checkbox"/> energy dispersive <input type="checkbox"/> wavelength dispersive</p> <p>Sample preparation: <input type="checkbox"/> pressed powder <input type="checkbox"/> fused glass disk</p>								

Tests performed by _____ Date _____
 Tests reported by _____ Title _____
 Phone _____ FAX _____ CCRL laboratory number _____







**CCRL PROFICIENCY SAMPLE PROGRAM
PORTLAND CEMENT SAMPLES NO. 183 AND NO. 184
PRIMARY CHEMICAL ANALYSIS REPORT FORM**

RETURN TO: R.K. Haupt, Supervisor, PSP
Cement and Concrete Reference Laboratory
4441 Buckeystown Pike, Ste C
Frederick, Maryland 21704
Fax: 610-834-7066

FROM: _____

e-mail: _____
Check here if name or address has changed _____

	Sample No. 183	Sample No. 184	Test ID	X-ray *	ASTM Reference Wet Method	ASTM Reference Wet Method	A.A.	Other (specify)
Report values below to nearest 0.001%				Check the method used				
Sodium oxide, Na ₂ O			90	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Phosphorus pentoxide, P ₂ O ₅			102	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Zinc oxide, ZnO			99	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Manganic oxide, Mn ₂ O ₃			101	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Chloride, Cl			104	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Chromium oxide, Cr ₂ O ₃			105	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<p>*Please provide the following information the XRF equipment used for these results.</p> <p>XRF instrument: <input type="checkbox"/> energy dispersive <input type="checkbox"/> wavelength dispersive</p> <p>Sample preparation: <input type="checkbox"/> pressed powder <input type="checkbox"/> fused glass disk</p>								

Carbon dioxide, CO ₂			97	Report vale to nearest 0.01%				
<p>Method used to determine CO₂ (as described in Appendix X2 of C114) -</p> <p><input type="checkbox"/> Split loss on ignition <input type="checkbox"/> Thermogravimetric analysis (TGA) <input type="checkbox"/> ASTM Test method C 25, section 22</p> <p><input type="checkbox"/> XRF <input type="checkbox"/> Combustion by induction furnance/IR <input type="checkbox"/> ASTM Test method E 350 <input type="checkbox"/> Other</p>								
Limestone content in portland cement			98	Report values to nearest 0.1%				
CO ₂ content in limestone			These values used in calculation of limestone content					

Potential Cement Phase Composition - Bogue calculations (as described in Annex A1 of ASTM C150-11)								
Tricalcium silicate, C ₃ S			106	Report values to nearest 0.1%				
Dicalcium silicate, C ₂ S			107					
Tricalcium aluminate, C ₃ A			108					
Tetracalcium aluminoferrite, C ₄ AF			109					

Tests performed by _____ Date _____
 Tests reported by _____ Title _____
 Phone _____ FAX _____ CCRL laboratory number _____

**CCRL PROFICIENCY SAMPLE PROGRAM
PORTLAND CEMENT SAMPLES NO. 183 AND NO. 184
PHYSICAL TESTS REPORT FORM**

RETURN TO: R.K. Haupt, Supervisor, PSP
Cement and Concrete Reference Laboratory
4441 Buckeystown Pike, Ste C
Frederick, Maryland 21704
Fax: 610-834-7066

FROM: _____

e-mail: _____
Check here if name or address has changed _____

TEST RESULTS
Report as Indicated in ()

	<u>Sample No.</u> 183	<u>Sample No.</u> 184	
NORMAL CONSISTENCY:			
Water (<i>nearest 0.1 percent by weight of cement</i>)	_____	_____	[110]
VICAT TIME OF SETTING:			
Initial Set, Report in minutes (<i>nearest 5 minutes</i>)	_____	_____	[120]
Final Set, Report in minutes (<i>nearest 5 minutes</i>)	_____	_____	[121]
Is automated Vicat Instrument used? <input type="checkbox"/> yes <input type="checkbox"/> no			
Manufacturer of automated Vicat: _____			
GILLMORE TIME OF SETTING:			
Initial Set, Report in minutes (<i>nearest 5 minutes</i>)	_____	_____	[130]
Final Set, Report in minutes (<i>nearest 5 minutes</i>)	_____	_____	[140]
FALSE SET (PASTE METHOD):			
Final Penetration / Initial Penetration (<i>nearest percent</i>)	_____	_____	[150]
AUTOCLAVE EXPANSION:	<u>No. 183</u>	<u>No. 184</u>	
Final Reading	_____	_____	
Initial Reading	_____	_____	
Difference	_____	_____	
Percent Expansion (<i>nearest 0.01 percent</i>)	_____	_____	[160]
AIR ENTRAINMENT:			
Percent Air (<i>nearest 0.1 percent</i>)	_____	_____	[170]
Mixing water (<i>nearest 0.1 percent by weight of cement</i>)	_____	_____	[180]
Flow Obtained (<i>nearest percent</i>)	_____	_____	[190]

Tests performed by _____ Date _____
 Tests reported by _____ Title _____
 Phone _____ Fax _____ CCRL Laboratory Number _____

**CCRL PROFICIENCY SAMPLE PROGRAM
 PORTLAND CEMENT SAMPLES NO. 183 AND NO. 184
 PHYSICAL TESTS REPORT FORM**

RETURN TO: R.K. Haupt, Supervisor, PSP
 Cement and Concrete Reference Laboratory
 4441 Buckeystown Pike, Ste C
 Frederick, Maryland 21704
 Fax: 610-834-7066

FROM: _____

 e-mail: _____
 Check here if name or address has changed _____

TEST RESULTS
 Report as Indicated in ()

	<u>No. 183</u>	<u>No.184</u>	Sample No. 183	Sample No. 184	
COMPRESSIVE STRENGTH:					
3-day, total load, lbs.	1) _____	_____			
	2) _____	_____			
	3) _____	_____			
Average 3-day strength (<i>nearest 10 psi</i>)	_____	_____	_____	_____	[200]
7-day, total load, lbs.	1) _____	_____			
	2) _____	_____			
	3) _____	_____			
Average 7-day strength (<i>nearest 10 psi</i>)	_____	_____	_____	_____	[210]
28-day, total load, lbs.	1) _____	_____			
	2) _____	_____			
	3) _____	_____			
Average 28-day strength (<i>nearest 10 psi</i>)	_____	_____	_____	_____	[211]
Flow Obtained for compressive strength mortar - constant water (<i>nearest percent</i>) ..	_____	_____	_____	_____	[230]

Information on cube molds and sealants (used for informational purposes only):

Type of cube mold: cube mold NOT clamped to base plate cube mold clamped to base plate
 Type of sealant used between cube mold and base plate:
 wax grease other - please specify _____

FINENESS:

Air Permeability, (<i>nearest 1 m²/kg</i>)	_____	_____	[270]
Wagner Turbidimeter, (<i>nearest 1 m²/kg</i>)	_____	_____	[280]
45 µm (No. 325) Sieve, Corrected percent passing (<i>nearest 0.01 percent</i>)	_____	_____	[281]
	<u>No. 183</u>	<u>No. 184</u>	
Correction Factor for 45 µm sieve (<i>nearest 0.1 percent</i>)	_____	_____	

Tests performed by _____ Date _____
 Tests reported by _____ Title _____
 Phone _____ Fax _____ CCRL Laboratory Number _____

**CCRL PROFICIENCY SAMPLE PROGRAM
 PORTLAND CEMENT SAMPLES NO. 183 AND NO. 184
 C1038 REPORT FORM**

RETURN TO: R.K. Haupt, Supervisor, PSP
 Cement and Concrete Reference Laboratory
 4441 Buckeystown Pike, Ste C
 Frederick, Maryland 21704
 FAX: 610-834-7066

FROM: _____

 e-mail: _____
Check here if name or address has changed _____

C1038 EXPANSION OF PORTLAND CEMENT MORTAR BARS STORED IN WATER

	Sample No. 183				Sample No. 184			
	Bar				Bar			
	#1	#2	#3	#4	#1	#2	#3	#4
Final reading								
Initial reading								
Difference (final - initial)								
Expansion (<i>nearest 0.001%</i>)								
Average expansion <i>(nearest 0.001%)</i> [400]								
C1038 Mortar - Mix water [401] <i>(nearest millilitre)</i>								
C1038 Mortar - Flow [402] <i>(nearest percent)</i>								

Tests performed by _____ Date _____
 Tests reported by _____ Title _____
 Phone _____ Fax _____ CCRL Laboratory Number _____

**CCRL PROFICIENCY SAMPLE PROGRAM
PORTLAND CEMENT SAMPLES NO. 183 AND NO. 184
HEAT OF HYDRATION REPORT FORM**

RETURN TO: R.K. Haupt, Supervisor, PSP
Cement and Concrete Reference Laboratory
4441 Buckeystown Pike, Ste C
Frederick, Maryland 21704
Fax: 610-834-7066

FROM: _____

e-mail: _____
Check here if name or address has changed _____

C186 HEAT OF HYDRATION OF HYDRAULIC CEMENT

	Sample No. <u>183</u>	Sample No. <u>184</u>	
HEAT OF SOLUTION:			
Dry Cement, cal/g (<i>nearest 0.1 cal/g</i>)	_____	_____	[291]
Partially hydrated, 7-day cal/g (<i>nearest 0.1 cal/g</i>)	_____	_____	[292]
Partially hydrated, 28-day cal/g (<i>nearest 0.1 cal/g</i>)	_____	_____	[301]
HEAT OF HYDRATION:			
7-day, cal/g (<i>nearest 0.1 cal/g</i>)	_____	_____	[290]
28-day, cal/g (<i>nearest 0.1 cal/g</i>)	_____	_____	[300]

C1702 HEAT OF HYDRATION BY ISOTHERMAL CONDUCTION CALORIMETRY

	Sample No. <u>183</u>	Sample No. <u>184</u>	
3-day, J/g (<i>nearest 1 J/g</i>)	_____	_____	[500]
7-day, J/g (<i>nearest 1 J/g</i>)	_____	_____	[510]

Method Used:

- Method A - sample and water are both temperature equilibrated and mixed inside the calorimeter.
- Method B - sample is mixed outside of the calorimeter then put into the calorimeter.

Instrument Used:

Manufacturer: _____
Model: _____

Tests performed by _____ Date _____
Tests reported by _____ Title _____
Phone _____ Fax _____ CCRL Laboratory Number _____

**CCRL PROFICIENCY SAMPLE PROGRAM
 PORTLAND CEMENT SAMPLES NO. 183 AND NO. 184
 SECONDARY CHEMICAL ANALYSIS REPORT FORM**

RETURN TO: R.K. Haupt, Supervisor, PSP
 Cement and Concrete Reference Laboratory
 4441 Buckeystown Pike, Ste C
 Frederick, Maryland 21704
 Fax: 610-834-7066

FROM: _____

 e-mail: _____
 Check here if name or address has changed _____

SECONDARY CHEMICAL ANALYSIS

Note: A final report on these results will not be provided to your laboratory unless you subscribe to the Secondary Chemical Analysis program. More information about this program and how to enroll in the program is available on the page titled "Information on CCRL Portland Chemical Analysis Program".

	Sample No. 183	Sample No. 184	Test ID	X-ray *	ASTM Alternate Wet Method	ASTM Reference Wet Method	A.A.	Other (specify)
Report values below to nearest 0.01%				Check the method used				
Silicon dioxide, SiO ₂			10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Aluminum oxide, Al ₂ O ₃			21	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Ferric oxide, Fe ₂ O ₃			30	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Calcium oxide, CaO			40	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Free Calcium oxide			41	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Magnesium oxide, MgO			50	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Sulfur trioxide, SO ₃			60	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Loss on ignition			70	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Briefly describe LOI procedure:								
Insoluble residue			80	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Potassium oxide, K ₂ O			100	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Titanium dioxide, TiO ₂			103	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<p>*Please provide the following information the XRF equipment used for these results.</p> <p>XRF instrument: <input type="checkbox"/> energy dispersive <input type="checkbox"/> wavelength dispersive</p> <p>Sample preparation: <input type="checkbox"/> pressed powder <input type="checkbox"/> fused glass disk</p>								

Tests performed by _____ Date _____
 Tests reported by _____ Title _____
 Phone _____ FAX _____ CCRL laboratory number _____







**CCRL PROFICIENCY SAMPLE PROGRAM
PORTLAND CEMENT SAMPLES NO. 183 AND NO. 184
SECONDARY CHEMICAL ANALYSIS REPORT FORM**

RETURN TO: R.K. Haupt, Supervisor, PSP
Cement and Concrete Reference Laboratory
4441 Buckeystown Pike, Ste C
Frederick, Maryland 21704
Fax: 610-834-7066

FROM: _____

e-mail: _____
Check here if name or address has changed _____

	Sample No. 183	Sample No. 184	Test ID	X-ray *	ASTM Reference Wet Method	ASTM Reference Wet Method	A.A.	Other (specify)
Report values below to nearest 0.001%				Check the method used				
Sodium oxide, Na ₂ O			90	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Phosphorus pentoxide, P ₂ O ₅			102	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Zinc oxide, ZnO			99	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Manganic oxide, Mn ₂ O ₃			101	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Chloride, Cl			104	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Chromium oxide, Cr ₂ O ₃			105	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<p>*Please provide the following information the XRF equipment used for these results.</p> <p>XRF instrument: <input type="checkbox"/> energy dispersive <input type="checkbox"/> wavelength dispersive</p> <p>Sample preparation: <input type="checkbox"/> pressed powder <input type="checkbox"/> fused glass disk</p>								

Carbon dioxide, CO ₂			97	Report vale to nearest 0.01%				
<p>Method used to determine CO₂ (as described in Appendix X2 of C114) -</p> <p><input type="checkbox"/> Split loss on ignition <input type="checkbox"/> Thermogravimetric analysis (TGA) <input type="checkbox"/> ASTM Test method C 25, section 22</p> <p><input type="checkbox"/> XRF <input type="checkbox"/> Combustion by induction furnance/IR <input type="checkbox"/> ASTM Test method E 350 <input type="checkbox"/> Other</p>								
Limestone content in portland cement			98	Report values to nearest 0.1%				
CO ₂ content in limestone				These values used in calculation of limestone content				

Potential Cement Phase Composition - Bogue calculations (as described in Annex A1 of ASTM C150-11)								
Tricalcium silicate, C ₃ S			106	Report values to nearest 0.1%				
Dicalcium silicate, C ₂ S			107					
Tricalcium aluminate, C ₃ A			108					
Tetracalcium aluminoferrite, C ₄ AF			109					

Tests performed by _____ Date _____
 Tests reported by _____ Title _____
 Phone _____ FAX _____ CCRL laboratory number _____