Masonry Cement Samples 95 & 96

Please Note:

- Please allow until August 1st for receipt of samples.
- Both cements are Type N, ASTM C91 Masonry cements.
- Determine the density of these masonry cements. Use these densities in the air content calculations.

How to Submit Test Results:

- On the CCRL Home Page, enter your lab number and PIN and click on "SIGN IN".
- Click on "Masonry Cement" from the menu on the left.
- Click on "Enter Data"
- Make sure the information at the top of the screen is accurate.
- Carefully enter your data. Round data properly. Data that is not rounded correctly cannot be submitted until correction is made. You will receive an error saying you have bad data, and the data will not be entered into the website.
- DO NOT enter "N/A" or zeros for data that you are not reporting, leave this data area blank. Zeros will be interpreted as data.
- Once all data has been entered click on the "Submit" button.
- You should see a confirmation screen. Print the confirmation screen for your records.
- If you have trouble entering or do not receive confirmation visit Data Entry
 Trouble Shooting or contact CCRL via ccrl@astm.org or by calling 240-4364800, prior to the closing date. CCRL cannot make accommodations for
 data received after the closing date.
- Sign out of the website and login again to check that your data was submitted properly. You may add data or make corrections up to the closing date.
- Closing date for submitting test results September 12, 2025.



www.ccrl.us

July 11, 2025

TO: Participants in the CCRL Masonry Cement Proficiency Sample Program

SUBJECT: Masonry Cement Proficiency Samples No. 95 and No. 96

The current pair of Masonry Cement Proficiency Samples are being forwarded by FedEx Ground to domestic addresses. Various methods are being used for international shipments. These samples are packaged in separate boxes and each contains approximately 7,500 grams of material. The boxes are labeled to identify the sample. You must label each bag of cement with the sample number when removing the cement from the box.

Please allow until August 1, 2025, for receipt of these samples (non-receipt date). Please weigh these bags to ensure that you have received the proper amount of each material. If the samples have not been received on this date or if the samples you received were damaged, you need to notify us in writing, so please email us at ccrl@astm.org. Replacement samples will be sent. testing. Additional shipping charges will be incurred if contact is not made by the non-receipt date.

These tests should be conducted as soon as possible after the samples are received, and the test results should be promptly reported to CCRL upon completion of testing. Test results should be entered at our website: www.ccrl.us.

A final report containing scatter diagrams, average values, standard deviations, laboratory ratings and other pertinent information will be available at our website. Notice and information about the final report will be sent by email.

Instructions covering the proposed tests, and the necessary data sheets for reporting the test results are on the following pages. Please read these carefully before testing.

Additional samples of this sample pair will be available for sale after the final report has been issued. Past CCRL samples for other programs are also available for sale. These samples can be used for research, technician training, and test equipment verification. Contact us for availability and pricing.

Sincerely,

Kent Niedzielski Program Manager Proficiency Sample Programs Cement and Concrete Reference Laboratory

CCRL PROFICIENCY SAMPLE PROGRAM MASONRY CEMENT SAMPLES NO. 95 AND NO. 96

INSTRUCTIONS FOR TESTING

The two samples for the tests are packaged in separate boxes, each of which contains approximately 7,500 grams of cement. The material for the odd numbered sample represents one cement, and the material for the even numbered sample represents another cement. The odd and even numbered samples should not be combined. Both cements are ASTM C91 Type N Masonry Cement. Prepare mortar in accordance with Section 14 and Table 2 of C91-23.

TESTS

Prior to testing, pass the cement for the tests through a No. 20 sieve in accordance with ASTM Standard C183.

Insofar as your laboratory is prepared to do so, make indicated tests on each sample in accordance with the current ASTM Methods designated below, but as <u>modified by ASTM C91-23</u>

Normal Consistency	ASTM C187-23
Time of Setting, Gillmore	ASTM C266-21
Soundness, Autoclave	ASTM C151-23
Air Content	ASTM C185-20
Compressive Strength (6 cube batch)	ASTM C109-23
Fineness, by the 45-µm Sieve	ASTM C430-17
Water Retention	ASTM C1506-17
Density	ASTM C188-17(23)

It is preferred that the same operator performs the same tests on both samples, on the same day. The results of a single determination should be reported rather than the average of duplicate determinations.

INSTRUCTIONS FOR REPORTING

For the sake of uniformity, report the values for the various tests to the nearest significant number indicated on the reporting forms.

Test results should be entered at our website: www.ccrl.us.

CCRL PROFICIENCY SAMPLE PROGRAM MASONRY CEMENT TESTS REPORT FORM SAMPLES NO. 95 & No. 96

RETURN TO: Kent Niedzielski, Program Manager Proficiency Sample Programs Cement and Concrete Reference Laboratory 4441 Buckeystown Pike, Suite C		FROM:	FROM:			
						<u> </u>
Frederick, Maryland 21704 Email: ccrl@astm.org Enter test results at our website: www.ccrl	<u>.us</u>	e-mail:				<u> </u>
	Report	TEST RESULTS Results as Indicate	d in ()		Sample No.	
NORMAL CONSISTENCY: Water (nearest 0.1 percent by weight	of cement)			<u>95</u>		[110]
GILMORE TIME OF SETTING: Initial Set, Report in minutes (neares	st 5 minutes). t 5 minutes)					[130] [140]
AUTOCLAVE EXPANSION: Final Reading Initial Reading Difference Percent Expansion (nearest 0.01 percent)						[160]
AIR ENTRAINMENT: Percent Air (nearest 0.1 percent) Mixing Water (nearest 0.1 percent by Flow Obtained (nearest percent)	weight of ce	ment)		•• -		[170] [180] [190]
Compressive Strength: 7-day, total load, lbs. 2	No. 95))	<u>No. 96</u>				
Average <i>(nearest 10 psi)</i>						[210]
Average (peerent 10 pei))					[211]
FINENESS: 45-µm (No. 325) Sieve, correct (nearest 0.01 percent)						[281]
Correction Factor for 45 µm sieve (nearest 0.1 percent)	<u>No. 95</u>	<u>No. 96</u>				[]
DENSITY: (nearest 0.01 g/cm³)						[310]
Tests performed by Tests reported by						
Phone F	Fax		CCRL La	boratory Number		

CCRL PROFICIENCY SAMPLE PROGRAM MASONRY CEMENT TESTS REPORT FORM SAMPLES NO. 95 & No. 96

RETURN TO: Kent Niedzielski, Proficiency Sample Programs Cement and Concrete Referer	-	FROM:		
4441 Buckeystown Pike, Suite Frederick, Maryland 21704 Email: ccrl@astm.org Enter test results at our websit	C C			
		ST RESULTS Ills as Indicated in ()	Sample No. 95	Sample No.
Initial flow (nearest perce Final flow (nearest percer Water retention (nearest Type of Vacuum Indicator	percent by weight of cement, nt) nt) nt) percent) r used with Water Retention A and number): □ Humboldt □ other (please s	Apparatus: □ vacuum gage	□ r	[331] [332] [333] mercury manometer
Tests performed by		Date		
Tests reported by Phone	Fax	Title	oratory Number	